

INSULCOAT 150FF AND 180 FF

European directive on Chemicals No. 1907/ 2006 (REACH) – products that are considered as articles are not compulsory in term of REACH regulation.

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Insulcoat 150 FF and 180 FF (Fiber Free) coating

Identification of the suppliers

INSULCON B.V.

P.O. Box 134

4650 AC STEENBERGEN, The Netherlands

Zilverhoek 4, 4651 SP STEENBERGEN

Tel. : +31 (0)167-565750

Fax : +31 (0)167-566263

www.insulcon.com

KERAMAB N.V.

Belgium

Tel. : + 32 (0)3 711.02.78

INSULCON GmbH

Germany

Tel.: + 49 (0)2131-408548-0

2. HAZARDS IDENTIFICATION

No particular hazards known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition

Chemical composition: SiO₂ – 54-55% - Al₂O₃ 40-44%, Fe₂O₃ – 1-2%

4. FIRST AID MEASURES

General

No special pre-cautions necessary

In the event of splashes or contact with skin.

This product normally does not rinse the skin. If it does, wash immediately with plenty of water.

After contact with eyes:

In case of contact with eyes rinse thoroughly with plenty of water.

After inhaling

Supply fresh air

After ingestion

When swallowed seek consult a physician.

Insulcon B.V.- The Netherlands - Tel: +31 (0)167 565 750

Insulcon GmbH - Germany - Tel: +49 (0)2131 408548-0

Keramab N.V. – Belgium - Tel: +32 (0)3 711 02 78

INSULCON

LEADER IN HIGH TEMPERATURE SOLUTIONS

KERAMAB

LEADER IN HIGH TEMPERATURE SOLUTIONS

www.insulcon.com / www.keramab.com

Form: C4-022

Effective: 30112018/ES/ka

Supersedes:15022013/ES/ka

All Rights Reserved

INSULCOAT 150FF AND 180 FF

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media. No special pre-cautions necessary

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:

Avoid dust otherwise, no special pre-cautions necessary

7. HANDLING AND STORAGE

No special precautions necessary

Shelf life

Approximately 12 months, based on unopened material kept in cool, dry storage conditions. Excessive heat will shorten shelf life and repeated freezing will damage the product. Storage between 5°C and 20°C is recommended.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ensure good ventilation, avoid dust.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Paint
Color	: Off White / Grey / Black
Odor	: Odorless
Density	: 1.72 g/cm ³
Solubility in water	: None

10. STABILITY AND REACTIVITY

Hazardous reactions:

No hazardous reactions when stored and handled according to prescribed instructions.

11. TOXICOLOGICAL INFORMATION

No toxicological chronically effect, if used according to description.

INSULCOAT 150FF AND 180 FF

12. ECOLOGICAL INFORMATION

No special precautions necessary

13. DISPOSAL CONSIDERATIONS

Product:

Dispose of in accordance with local authority regulations

14. TRANSPORT INFORMATION

No special precautions necessary

15. REGULATORY INFORMATION

Labelling in accordance with EC-Directives:

No label required according to EU-Directives

S-Phrases

S22

S25

16. OTHER INFORMATION

None